



Rack Mount Modem RMM Series

External 56k Dial-Up Modem for 19" Racks

Out-of-Band Access:

- Dial-Up Rack Modem for Out-of-Band Management
- Out-of-the-Box Ready to Answer on x1 Ring
- Dual Redundant Power Inputs

Modem Features:

- 56K v.92 Internal Modem
- DB9F, DB25F & RJ45 Modem Ports
- Hayes™ Standard AT Modem Commands
- AC & DC Models Available



RMM-56K (100-240VAC)



RMM-56K-DC (± 18-72V DC)

Specifications:	
Modem:	56K v.92 Internal Modem
Modem Ports:	(1) RJ45 Connector (DCE Pinout) (1) DB9F Connector (DCE Pinout) (1) DB25F Connector (DCE Pinout)
Phone Line Port:	(1) RJ11 for connection to Telco Line
Operating Temperature:	32°F - 122°F (0°C - 50°C)
Power:	RMM-56K Model: (2) IEC-320-C14 Inlets, 100 to 240 VAC, 50/60 Hz, 0.2 Amp Max. RMM-56K-DC Model: (2) ±18 - 72V DC Inputs Terminal Strip (#6-32) 0.2 Amp Max.
Humidity:	10 - 90% RH
Size:	Height: 1.75" (4.4 cm), 1 Rack U Width: 19.00" (48.3 cm) Depth: 4.6" (11.7 cm)
Shipping Weight:	4 Lbs (3.6 Kgs)
Mounting:	19" Rack Brackets Included
Approvals:	UL, cUL, CE, FCC Class A

- ✓ 5 Year Warranty
- ✓ Stocked for Same Day Shipments
- ✓ In-House Design & Manufacturing
- ✓ Made In USA



Visit www.wti.com For More Info

Toll Free:	Direct:	FAX:
(800) 854-7226	(949) 421-4199	(949) 583-1320

